

Claims

cancelled

1. (~~withdrawn~~) A non-linear transmission line, comprising:
a non-parallel waveguide; and
a plurality of varactors in electrical communication with the non-parallel waveguide.

cancelled

2. (~~withdrawn~~) The non-linear transmission line of claim 1, wherein the plurality of varactors are configured to temporally reduce a signal applied to the non-linear transmission line.

cancelled

- PN 3. (~~withdrawn~~) The non-linear transmission line of claim 2, wherein the varactors are Schottky diodes.

cancelled

4. (~~withdrawn~~) The non-linear transmission line of claim 1, wherein the varactors are Schottky diodes.

cancelled

5. (~~withdrawn~~) The non-linear transmission line of claim 1, further comprising a semiconductor substrate and wherein the non-parallel guide is fixed with respect to the semiconductor substrate.

cancelled

6. (~~withdrawn~~) The non-linear transmission line of claim 5, wherein the varactors are Schottky mesa diodes defined on the semiconductor substrate.

cancelled

7. (~~withdrawn~~) A non-linear transmission line, comprising:
a plurality of varactors; and
an enhanced-delay waveguide in electrical communication with the plurality of varactors.

cancelled

8. (~~withdrawn~~) The non-linear transmission line of claim 7, wherein the varactors are situated so that the non-linear transmission line is a shockline.

cancelled

9. (~~withdrawn~~) A non-linear transmission line, comprising:
a substrate;
a plurality of varactors; and
a waveguide defined with respect to the substrate, the waveguide including an airbridged portion configured to control a waveguide propagation characteristic.

cancelled

10. (~~withdrawn~~) The non-linear transmission line of claim 9, wherein the waveguide is a non-parallel waveguide.

PN

cancelled

11. (~~withdrawn~~) The non-linear transmission line of claim 10, wherein the non-parallel waveguide includes a conductor that is airbridged and is electrically connected to the plurality of varactors so as to temporally reduce an electrical signal applied to the non-linear transmission line.

cancelled

12. (~~withdrawn~~) The non-linear transmission line of claim 10, wherein the non-parallel waveguide includes a gap configured to receive the plurality of varactors so as to temporally reduce an electrical signal applied to the non-linear transmission line.

cancelled

13. (~~withdrawn~~) The non-linear transmission line of claim 9, wherein portions of the conductors are substantially airbridged near the plurality of varactors.

cancelled

14. (~~withdrawn~~) The non-linear transmission line of claim 9, wherein the waveguide is a non-parallel waveguide that includes a first conductor and a second conductor.

cancelled

15. (~~withdrawn~~) The non-linear transmission line of claim 14, wherein at least one of the first conductor and the second conductor includes at least one linear segment.

cancelled

16. (~~withdrawn~~) The non-linear transmission line of claim 9, wherein the waveguide is a non-parallel waveguide that includes a periodically repeated waveguide section.

cancelled

17. (~~withdrawn~~) A non-linear transmission line configured to temporally reduce an electrical signal, comprising:

a semiconductor substrate;

a non-parallel waveguide; and

a plurality of semiconductor junctions distributed along the non-parallel waveguide and electrically connected to the non-parallel waveguide.

cancelled

PN 18. (~~withdrawn~~) The non-linear transmission line of claim 17, wherein the non-parallel waveguide includes a first conductor and a second conductor, wherein the plurality of semiconductor junctions are electrically connected to the first conductor and the second conductor.

cancelled

19. (~~withdrawn~~) An electrical pulse generator, comprising:

a pulse source configured to produce an unprocessed electrical pulse;

a mode converter configured to receive portions of the unprocessed electrical pulse at a first input and a second input, and to provide a processed electrical signal at a first output and a second output, wherein the processed electrical signal is a differential electrical signal

cancelled

20. (~~withdrawn~~) The electrical pulse generator of claim 19, wherein the mode converter includes:

(a) a first waveguide configured to deliver a portion of the unprocessed electrical signal to the first output;

(b) a second waveguide configured to receive a portion of the unprocessed electrical signal; and

(c) an inverting waveguide configured to invert the portion of the unprocessed electrical signal received from the second waveguide and to deliver the inverted portion to the second

output, whereby a processed electrical signal is delivered to the first output and the second output.

cancelled

21. ~~(withdrawn)~~ The electrical pulse generator of claim 20, wherein the first, second, and inverting waveguides are coaxial cables.

cancelled

22. ~~(withdrawn)~~ The electrical pulse generator of claim 21, wherein the second and inverting waveguides include respective inner conductors and outer conductors, and the inner conductor and the outer conductor of the second waveguide are electrically connected to the outer conductor and the inner conductor, respectively, of the inverting conductor.

cancelled

PN 23. ~~(withdrawn)~~ The electrical pulse generator of claim 21, further comprising a mode filter configured to enhance a magnitude of a differential mode electrical signal in the processed electrical signal

cancelled

24. ~~(withdrawn)~~ The electrical pulse generator of claim 21 further comprising a shockline configured to receive portions of the unprocessed electrical signal from the first input waveguide and the inverting waveguide and to produce a temporally reduced electrical signal.

cancelled

25. ~~(withdrawn)~~ A pulse generator, comprising:
a pulse source that produces an electrical pulse; and
a non-linear transmission line that includes a non-parallel waveguide and a plurality of varactors in electrical communication with the non-parallel waveguide, wherein the non-linear transmission line is configured to receive the electrical pulse and deliver a processed electrical pulse.

cancelled

26. ~~(withdrawn)~~ The pulse generator of claim 25 wherein the processed electrical pulse is temporally reduced.

canceled

27. (~~withdrawn~~) A mode filter for producing a differential pulse, comprising:
a first waveguide; and

a second waveguide, wherein a common mode impedance of the first waveguide and a common mode impedance of the second waveguide are mismatched and a differential mode impedance of the first waveguide and a differential mode impedance of the second waveguide are matched.

canceled

28. (~~withdrawn~~) The mode filter of claim 27, wherein the common mode impedance of the first waveguide is about 25 Ohms and the common mode impedance of the second waveguide at least about 100 Ohms.

PN

canceled

29. (~~withdrawn~~) The mode filter of claim 28, wherein the differential mode impedances of the first waveguide and the second waveguide are approximately equal.

canceled

30. (~~withdrawn~~) The mode filter of claim 29, where the differential mode impedances are about 50 Ohms.

canceled

31. (~~withdrawn~~) An apparatus for electrically connecting a transmission line interior conductor to a conductor pad on a substrate, comprising:

a rod configured to contact the interior conductor; and

a spring configured to urge the rod toward the interior conductor, thereby urging the transmission line conductor towards the conductor pad.

canceled

32. (~~withdrawn~~) An apparatus for electrically connecting to a substrate, comprising:
an airline that includes an airline conductor and an airline housing, wherein the airline conductor is situated within the airline housing; and
means for urging the airline conductor towards the substrate.

- 1
33. (original) A sampler, comprising:

a signal conductor;
a sampling diode in electrical communication with the signal conductor; and
a non-linear transmission line that includes a non-parallel waveguide and a plurality of varactors, the non-linear transmission line configured to deliver sampling strobe pulses to the sampling diode.

² ~~34~~. (original) The sample of claim ¹~~33~~, further comprising an intermediate frequency (IF) waveguide configured to electrically connect to the signal conductor as controlled by the sampling diode.

³ ~~35~~. (original) The sampler of claim ²~~34~~, further comprising a measurement system configured to receive portions of an electrical signal applied to the signal conductor from the IF waveguide.

⁴ ~~36~~. (original) The sampler of claim ³~~35~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

⁵ ~~37~~. (original) The sampler of claim ²~~34~~, further comprising a measurement system configured to receive portions of an electrical signal applied to IF waveguide from the signal conductor.

⁶ ~~38~~. (original) The sampler of claim ⁵~~37~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

⁷ ~~39~~. (original) The sampler of claim ¹~~33~~, wherein the non-linear transmission line includes a plurality of Schottky mesa diodes.

⁸ ~~40~~. (original) The sampler of claim ¹~~33~~, wherein the non-parallel waveguide includes at least one periodically repeated waveguide section.

⁹ 41. (original) The sampler of claim ¹33, further comprising a strobe waveguide transition configured to receive the sampling strobe pulses from the non-linear transmission line and to deliver enhanced strobe pulses to the sampling diode.

¹⁰ 42. (original) The sampler of claim ¹33, wherein the non-parallel waveguide is a slotline.

¹¹ 43. (original) The sampler of claim ¹33, wherein the non-parallel waveguide is a coplanar stripline.

¹² 44. (currently amended) A sampling circuit, comprising:

PN a first nonparallel waveguide configured to receive a sampling strobe and having a first impedance;

a second nonparallel waveguide configured to receive the sampling strobe from the first nonparallel waveguide and having a second impedance, wherein the first impedance and the second impedance are configured to produce an enhanced sampling strobe; and

at least one diode electrically controlled by the sampling strobe and configured to deliver a sampled portion of an input signal to an output conductor.

¹³ 45. (currently amended) The sampling circuit of claim ¹²44, wherein the second nonparallel waveguide includes a termination configured to direct an inverted portion of the enhanced sampling strobe to the sampling diode, thereby establishing a sampling window.

¹⁴ 46. (currently amended) The sampling circuit of claim ¹³45, wherein the first nonparallel waveguide and the second nonparallel waveguide are slotlines.

¹⁵ 47. (original) The sampling circuit of claim ¹³45, further comprising an IF waveguide configured to deliver the sampled portion to the output conductor.

cancelled

48. (~~withdrawn~~) A method of temporally reducing an electrical signal, comprising:
providing a non-linear transmission line that includes a non-parallel waveguide; and
directing the electrical signal to the non-linear transmission line.

cancelled

49. (~~withdrawn~~) A method of delivering an electrical signal to a substrate, comprising:
configuring an airline to receive the electrical signal; and
urging an interior conductor of the airline into electrical communication with the
substrate.

cancelled

50. (~~withdrawn~~) The method of claim 49, wherein the airline has a characteristic
impedance corresponding to a characteristic impedance of a transmission line from which the
electrical signal is received by the airline.

cancelled

PN 51. (~~withdrawn~~) The method of claim 50, wherein the characteristic impedance is about
50 Ohms.

cancelled

52. (~~original~~) A method of producing a differential pulse from a common mode pulse,
comprising:
splitting the common mode pulse into at least two portions; and
directing at least one portion to a common mode to differential mode converter.

16 53. (new) A sampler, comprising:

a signal conductor;
a sampling diode in electrical communication with the signal conductor; and
a non-linear transmission line that includes a non-parallel waveguide and a plurality of
varactors, the non-linear transmission line configured to deliver sampling strobe pulses to the
sampling diode, wherein the non-parallel waveguide includes at least one periodically repeated
waveguide section.

¹⁷~~54~~. (new) The sampler of claim ¹⁶~~53~~, further comprising an intermediate frequency (IF) waveguide configured to electrically connect to the signal conductor as controlled by the sampling diode.

¹⁸~~55~~. (new) The sampler of claim ¹⁷~~54~~, further comprising a measurement system configured to receive portions of an electrical signal applied to the signal conductor from the IF waveguide.

¹⁹~~56~~. (new) The sampler of claim ¹⁸~~55~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

PN ²⁰~~57~~. (new) The sampler of claim ¹⁷~~54~~, further comprising a measurement system configured to receive portions of an electrical signal applied to IF waveguide from the signal conductor.

²¹~~58~~. (new) The sampler of claim ²⁰~~57~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

²²~~59~~. (new) The sampler of claim ¹⁶~~53~~, wherein the non-linear transmission line includes a plurality of Schottky mesa diodes.

²³~~60~~. (new) The sampler of claim ¹⁶~~53~~, further comprising a strobe waveguide transition configured to receive the sampling strobe pulses from the non-linear transmission line and to deliver enhanced strobe pulses to the sampling diode.

²⁴~~61~~. (new) The sampler of claim ¹⁶~~53~~, wherein the non-parallel waveguide is a slotline.

²⁵~~62~~. (new) The sampler of claim ¹⁶~~53~~, wherein the non-parallel waveguide is a coplanar stripline.

²⁶~~63~~. (new) A sampler, comprising:

a signal conductor;

a sampling diode in electrical communication with the signal conductor; and

a non-linear transmission line that includes first, second, and third non-parallel waveguide sections having first, second, and third characteristic impedances, respectively, and a plurality of varactors, the non-linear transmission line configured to deliver sampling strobe pulses to the sampling diode.

²⁷~~64~~. (new) The sample of claim ²⁶~~63~~, further comprising an intermediate frequency (IF) waveguide configured to electrically connect to the signal conductor as controlled by the sampling diode.

PN ²⁸~~65~~. (new) The sampler of claim ²⁷~~64~~, further comprising a measurement system configured to receive portions of an electrical signal applied to the signal conductor from the IF waveguide.

²⁹~~66~~. (new) The sampler of claim ²⁸~~65~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

³⁰~~67~~. (new) The sampler of claim ²⁷~~64~~, further comprising a measurement system configured to receive portions of an electrical signal applied to IF waveguide from the signal conductor.

³¹~~68~~. (new) The sampler of claim ³⁰~~67~~, wherein the measurement system is configured to produce an equivalent-time representation of the electrical signal.

³²~~69~~. (new) The sampler of claim ²⁶~~63~~, wherein the non-linear transmission line includes a plurality of Schottky mesa diodes.

³³
~~70~~. (new) The sampler of claim ²⁶~~63~~, wherein at least one of the non-parallel waveguide sections is periodically repeated.

³⁴
~~71~~. (new) The sampler of claim ²⁶~~63~~, further comprising a strobe waveguide transition configured to receive the sampling strobe pulses from the non-linear transmission line and to deliver enhanced strobe pulses to the sampling diode.


³⁵
~~72~~. (new) The sampler of claim ²⁶~~63~~, wherein the non-parallel waveguide is a slotline.

³⁶
~~73~~. (new) The sampler of claim ²⁶~~63~~, wherein the non-parallel waveguide is a coplanar stripline.

Respectfully submitted,

KLARQUIST SPARKMAN, LLP

By



Michael D. Jones

Registration No. 41,879

One World Trade Center, Suite 1600
121 S.W. Salmon Street
Portland, Oregon 97204
Telephone: (503) 226-7391
Facsimile: (503) 228-9446